

LCN-T8

Cable Connection Set for Conventional Key Converters with Acoustic Device



Description:

The LCN-T8 is an LCN connection set of cables with an acoustic signal device for conventional potential-free sensors.

It is suited for use with the LCN-UPP, LCN-UPS or LCN-UP24 modules, it can however be used with the LCN-HU, LCN-SH and LCN-LD.

Each key connection distinguishes the "Hit, Hold and Release," function.

Field of application:

The LCN-T8 is a connection cable for a max. of 8 UP key converters for simple wiring in patress boxes.

It can also be used for two „multi-switches“ (with 4 single contacts).

Hardware equipment:

Cable with plug for T-Port connection

Litz wire connection with insulated ferrules for the key sensors

Acoustic signal device

Note:

The connecting cables between key sensor and the LCN-T8 must not exceed the maximum length of 0.5m. For longer cables the LCN-TU4R is available.


Not suitable for permanent contacts (switches, binary sensors,...)

LCN-T8

Cable Connection Set for Conventional Key Converters with Acoustic Detector

Dimensions:

Mass (W x L x H): 10mm x 22mm x 11mm
 Supply Cable: 160mm



Technical Data:

Connection:
 Cable type: litz wires 0,75 mm², with insulated ferrules

Inputs:
 Connection length: max. 0,5 Meter each input

General Details:
 Operating temperature: -10°C to +40°C
 Humidity: max. 80% rel., non condensing
 Environmental conditions: stationary installation according to VDE 632, VDE 637

Safety classification: IP 20, when installed in patress box

Assembly: De-centralized installation in deep patress box with the LCN-UPP

Circuit Diagram

